

SHIELD PEEL[®]

SHIELD IT TO PROTECT IT

WINDOWS

PEELSTRIP

For “How to Apply” videos &
more info on all our products:
www.shieldnpeel.com.au



www.gurucorp.com.au
Unit 2 / 872 Pacific Highway
TUGGERAH NSW 2250
Ph 1300 852 646



SHIELD n PEEL[®]

SHIELD IT TO PROTECT IT

WINDOWS



SHIELD n PEEL for **WINDOWS** delivers a temporary surface protection to most non-porous surfaces. It protects against possible damage caused by cement, paint or render spatter, welding and grinding flecks as well as other damage caused during the building, renovating and cleaning process.



USE ON

Windows
Glass
Powder-coated frames
Balustrades
Most non-porous surfaces *

PROTECTS FROM

Mortar, render, plaster, paint
Dirt, dust, mud & grime
Most solvents
Light impact
Acid rain
Grinding & welding flecks

*** ALWAYS TEST SURFACES FOR SUITABILITY BEFORE USE**



COVERAGE UP TO 4m² PER LITRE

For best results we recommend a coverage of 250µ WET (10mils WET) to achieve a coverage of approx. 4m² per litre.



PROTECTION PERIOD UP TO 6 MONTHS

NOTE: Coverage, cost and protection period are guides only as actual coverage, costs and protection periods achieved are determined by the substrate surface to be coated as well as the application technique used. For extended protection additional coats can be applied.

For "How to Apply" videos & more info on all our products: www.shieldnpeel.com.au

SAFETY

- | | |
|-------------------------------------|---|
| DO NOT TAKE INTERNALLY IF SWALLOWED | EYES & SKIN CONTACT |
| * DO NOT induce vomiting | * Flush thoroughly with plenty of water |
| * Drink plenty of water (slowly) | * If irritation persists, seek medical advice |
| * Seek medical advice | |

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

SHIELD N PEEL WINDOWS

PRODUCT USE

Waterborne Peelable coating.

SUPPLIER

Company:
Guru Corporation Pty Ltd
ABN: 83 096 593 092
Address: Unit 2 / 872 Pacific Highway, LISAROW NSW 2250, AUSTRALIA
Telephone: +61 2 4353 9660
Fax: +61 2 4353 9466

SECTION 2 - HAZARDS IDENTIFICATION

GHS Hazard Classified: Not Applicable

GHS Signal Word: Not Applicable

GHS Hazard Statements: Not Applicable

GHS Precautionary Statements: Product is not considered hazardous under normal conditions. Direct contact of product with eyes can cause irritation.

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

| CHEMICAL NAMES | CAS NO. | CONC, % | TWA (mg/m ³) | STEL (mg/m ³) |
|---------------------------------|-----------|---------|--------------------------|---------------------------|
| ACRYLIC POLYMER | SECRET | 30-60 | NOT SET | NOT SET |
| OTHER NON HAZARDOUS INGREDIENTS | VARIOUS | 10-30 | NOT SET | NOT SET |
| WATER | 7732-18-5 | to 100 | NOT SET | NOT SET |

SECTION 4 - FIRST AID MEASURES

EYES: The material can be removed with water. Remove contact lenses if possible and flush with plenty of water at least 30 minutes. Seek medical attention for inspection of the eye and the vicinity hereof.

SKIN: Immediate first aid is not likely to be required. The material can be removed with water. Flush with plenty of water while or after removing contaminated clothes and shoes. Wash contaminated clothing normally before reuse.

INGESTION: Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. A physician or Poison Control Center should be contacted for advice and observation.

INHALATION: Immediate first aid is not likely to be required.

You should call the Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

WINDOWS

SDS

DATASHEET

SECTION 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA:

Water spray, foam, dry chemical or carbon dioxide or halon.

SPECIAL FIRE FIGHTING PROCEDURES:

Firefighters, and others exposed, wear self-contained breathing apparatus. Equipment should be thoroughly decontaminated after use.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

None

HAZARDOUS DECOMPOSITION PRODUCTS:

Chemicals that may be formed if temperature, oxygen content and circumstances allows for it: hydrocarbons, carbon monoxide and carbon dioxide.

FLAMMABILITY:

Material must be heated locally to more than 380 C before ignition can occur.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES:

Personal precautions: Use personal protection measures as described in section 8.

Environmental precautions: Keep out of drains and water courses.

Methods of cleaning up: In case of spill: Scoop, sweep, or vacuum and remove.

Refer to section 13 for disposal information and 15 for reportable quantity information.

SECTION 7 - HANDLING AND STORAGE

HANDLING:

Handle in accordance with good industry hygiene and safety practices to minimize spill and water contamination. Vacuum using a wet vacuum cleaner. Avoid the use of compressed air for cleaning. Take precautionary measures to avoid electrostatic discharges. These practices include avoiding unnecessary exposure and removal of material from eyes, skin and clothing. Keep away from heat, sparks and open flame. Empty containers or bags retain vapor and product residue. Observe all recommended safety precautions until container is cleaned, reconditioned or destroyed. The use of this material's container for non-industrial purposes is prohibited and any reuse must be in consideration of the data provided in this SDS.

STORAGE:

Keep the containers tightly closed. Store in a cool – absolutely frost-free, dry place.

GENERAL:

Stable under normal conditions of handling and storage

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**ENGINEERING CONTROLS:****VENTILATION:**

If practical, use local mechanical exhaust ventilation at sources of air contamination such as processing equipment.

RESPIRATORY PROTECTION: This material is not likely to present an airborne exposure concern under normal conditions of use. If however sprayed in air by high-pressure to form an aerosol use the normal safety procedures and practice as is required by the process.

EYE PROTECTION: Use good industrial practice to avoid every eye contact.

SKIN PROTECTION: Although this product does not present a significant skin concern, minimize skin contamination by following good industrial practice. Wash thoroughly with soap after handling. Dried up PVB on skin normally is easily removed.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Wearing protective gloves is recommended. Consult the glove/clothing manufacturer to determine the appropriate type glove/clothing for a given application.

WORK HYGIENIC PRACTICES: Wearing protective gloves is recommended. Consult the glove/clothing manufacturer to determine the appropriate type glove/clothing for a given application. Use good industrial practice to avoid eye contact, by pouring, pumping or other change of container for the dispersion use protective goggles.

EXPOSURE GUIDELINES: Airborne exposure limits: (ml/m³ = ppm)

OSHA and/or ACGIH have not established specific exposure limits for this material. However, they have established limits for particulates not otherwise regulated (PNOR) and particulates not otherwise classified (PNOC) respectively, which are the least stringent exposure limits applicable to dusts:

Process measures: Provide adequate local and overall ventilation. Ventilate as needed to control airborne dust levels below the occupational safety limits. Provide access to running clean water or eye-rinsing stations, as well as frequent cleaning for spillage.

Respiratory protection: Use an approved respiratory unit and if uncontrolled releases have to be cleaned use a positive pressure respiratory system.

Eye protection: Wear safety glasses with side shields or goggles.

Hand protection: Wear resistant gloves of rubber or plastic.

Skin protection: Wear appropriate clothing to avoid prolonged skin-contact.

Hygiene: Always observe good personal hygiene, as washing after handling and before eating, drinking or smoking. Routinely wash clothing.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**PHYSICAL PROPERTIES**

| | |
|---------------------------------------|-----------------|
| BOILING POINT: | 212 F |
| Specific Gravity (H ₂ O=1) | 1.07 |
| % volatile by volume | 50 (water) |
| Vapor Density | N/A |
| Evaporation Rate | 100 C |
| Odor | Mild odor |
| Appearance | Blue liquid |
| Viscosity | 6,000-12000 cps |
| Odor Threshold | None |
| pH | >8 |
| Solubility in water | 100% soluble |

SECTION 10 - STABILITY & REACTIVITY

STABILITY

Stable. Shelf life depends on storage conditions. Agitation requires before use, phase separation may take place.

CONDITIONS TO AVOID (STABILITY): All sources of ignition and heat

INCOMPATIBILITY (MATERIAL TO AVOID): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Butyraldehyde; butyric acid; acrolein; crotonaldehyde; Methanol; formic acid; carbon monoxide (CO); carbon dioxide.

HAZARDOUS POLYMERIZATION: Hazardous polymerization does not occur.

CONDITIONS TO AVOID (POLYMERIZATION): Freeze and cold temperature.

SECTION 11 - TOXICOLOGICAL INFORMATION

Local Effects: There is no data to hand indicating any particular local effects.

Target Organs: There is no data to hand indicating any particular target organs.

CLASSIFICATION OF HAZARDOUS INGREDIENTS

| Ingredient | Risk Phrases |
|--|--------------|
| No ingredient mentioned in the HSIS Database is present in this product at hazardous concentrations. | |

POTENTIAL HEALTH EFFECTS

INHALATION:

Short Term Exposure: Available data indicates that this product is not harmful. However product may be mildly irritating, although unlikely to cause anything more than mild transient discomfort.

Long Term Exposure: No data for health effects associated with long term inhalation.

SKIN CONTACT:

Short Term Exposure: Available data indicates that this product is not harmful. It should present no hazards in normal use. However product may be mildly irritating, but is unlikely to cause anything more than mild discomfort which should disappear once contact ceases.

Long Term Exposure: No data for health effects associated with long term skin exposure.

EYE CONTACT:

Short Term Exposure: This product is believed to be mildly irritating, to eyes, but is unlikely to cause anything more than mild transient discomfort.

Long Term Exposure: No data for health effects associated with long term eye exposure.

INGESTION:

Short Term Exposure: Significant oral exposure is considered to be unlikely. However, this product is believed to be mildly irritating to mucous membranes but is unlikely to cause anything more than mild transient discomfort.

Long Term Exposure: No data for health effects associated with long term ingestion.

CARCINOGEN STATUS:

SWA: No significant ingredient is classified as carcinogenic by SWA.

NTP: No significant ingredient is classified as carcinogenic by NTP.

IARC: No significant ingredient is classified as carcinogenic by IARC.

SECTION 12 - ECOLOGICAL INFORMATION

Not conducted environmental toxicity, accumulation, mobility or biodegradation studies with this material, but recommends extensive use of recycling techniques for the product and waste products by the process in mention.

SECTION 13 - DISPOSAL CONSIDERATIONS

This material when discarded is not a hazardous waste as that term is defined by the Resource, Conservation and Recovery Act (RCRA), 40 CFR 261.

Disposal considerations: Incineration, Recycling or Landfill.

Miscellaneous advice: Local, state, provincial, and national disposal regulations may be more or less stringent.

This product should not be dumped, spilled, rinsed or washed into sewers or public waterways.

RCRA HAZARD CLASS: None known.

SECTION 14 - TRANSPORTATION INFORMATION

This product is not classified as a Dangerous Good by ADG, IATA or IMDG/IMSBC criteria. No special transport conditions are necessary unless required by other regulations.

SECTION 15 - REGULATORY INFORMATION

AICS: All of the significant ingredients in this formulation are compliant with NICNAS regulations.

SECTION 16 - OTHER INFORMATION**ACRONYMS**

| | |
|----------------------|--|
| ADG Code: | Australian Code for the Transport of Dangerous Goods by Road and Rail (7th edition). |
| AICES: | Australian Inventory of Chemical Substances. |
| SWA: | Safe Work Australia, formerly ASCC and NOHSC. |
| CAS Number: | Chemical Abstracts Service Registry Number. |
| Hazchem Code: | Emergency action code of numbers and letters that provide information to emergency services especially firefighters. |
| IARC: | International Agency for Research on Cancer. |
| NOS: | Not otherwise specified. |
| NTP: | National Toxicology Program (USA). |
| R-Phrase: | Risk Phrase. |
| SUSMP: | Standard for the Uniform Scheduling of Medicines & Poisons. |
| UN Number: | United Nations Number. |

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS.

OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

SHIELD N PEEL WINDOWS delivers quality temporary surface protection to most non-porous surfaces. SHIELD N PEEL WINDOWS protects against possible damage caused by cement, paint and render spatter, welding and grinding flecks as well as other damage caused during the building, renovating and cleaning process. Being water-based there is no need for harsh solvents or chemicals during clean up with rollers and spray guns washing out in water.

Great for protecting non-porous surfaces such as:

Windows
Glass
Powder-coated frames
Balustrades
Most non-porous surfaces *

*** ALWAYS TEST SURFACES FOR SUITABILITY BEFORE USE**

'Saves you time and money by eliminating costly replacement'

Allows natural light in
Water-based
Non-flammable
Non-hazardous
Biodegradable
Easy to apply & remove

TEST AREA

It is recommended that you first apply a test patch to ensure compatibility before proceeding with the entire job.

PREPARATION

- Application Surface **must** be clean & dry
- Use drop sheets and tape to protect nearby surfaces
- **Tools needed:**
Roller with a 20mm polyester NAP or airless spray gun

APPLICATION

- Stir thoroughly - for best results use electric drill with a paint stirrer
- Apply a thick even coat ensuring neat edges to avoid possible feathered edges
- Allow a border of 5-10mm around the surface to be coated. Be sure to apply liberally for ease of removal once product has dried and protection is no longer required
- If two coats are required, wait until first coat is touch dry before applying the second coat
- Ensure adequate ventilation when applying product
- For best application apply at temperatures between 14°C and 25°C. Avoid applying product if temperature is below 10°C or above 35°C
- Use a WET mils guide to ensure minimum mils are met

DRYING

Approx. 30 minutes (touch dry).
NOTE: Drying times are a guide only. Longer drying times may be required under cooler or humid conditions.

COVERAGE

For best results, a WET film thickness of 250 microns (10mils WET) is recommended achieving a coverage area of approx. 4m² per litre.

NOTE: Areas are a guide only as actual coverage achieved is determined by the substrate surface to be coated as well as the application technique used.

HOW LONG WILL THE PROTECTION LAST?

Based on the minimum recommended WET film thickness application of 250 microns on glass, SHIELD N PEEL WINDOWS can last up to 6 months, depending on climate conditions. Additional coats maybe applied where longer protection is required.

REMOVAL

- Start from a corner and carefully peel back the coating. If applied correctly, you should have enough tensile strength in the coating to remove it in one sheet.
- If necessary water may be used with the pressure of a hose or power sprayer to remove stubborn areas should they occur.
- Avoid removing the peelable coating in temperatures below 10°C as the film may be brittle and difficult to peel. Coating is best removed at temperatures between 14°C and 20°C.

DO NOT APPLY SHIELD N PEEL WINDOWS TO:

Fibreglass, acrylic, perspex, brick, concrete, timber, 'soft' Low-e (low emissivity) glass or any other porous surface.

PRECAUTION

- Avoid skin and eye contact.
- Chemical goggles and impervious gloves should be worn when handling this product.
- Avoid breathing vapors that occur during application. A painters mask or other suitable respiratory device should be work when applying this product
- DO NOT ALLOW PRODUCT TO FREEZE

CLEAN UP / WASTE

- Wash up in water
- DO NOT pour contents or washings down drains or sinks. Dispose of as per your local council regulations.

COLOUR

SHIELD N PEEL WINDOWS is blue in colour both wet and as a dry film.

SHELF LIFE / STORAGE

- Will keep up to 12 months if stored in a clean dry area above 10°C.
- Keep the lid sealed airtight when not in use.

Shield n Peel products are designed to be used on new surfaces that have unblemished, perfect finishes. Surfaces that are not new may be weathered or show signs of erosion making the surface rough or porous and therefore unsuitable for use with Shield n Peel products. These surfaces should be thoroughly tested with the Shield n Peel product and left for a sensible period of time to evaluate the products removability on the surface. Use of Shield n Peel products on these types of surfaces are done so with a clear understanding that the buyer assumes all risks and liabilities for the results of such use.



Shield n Peel products are designed to be used on new surfaces that have unblemished, perfect finishes. Surfaces that are not new may be weathered or show signs of erosion making the surface rough or porous and therefore unsuitable for use with Shield n Peel products. These surfaces should be thoroughly tested with the Shield n Peel product and left for a sensible period of time to evaluate the products removability on the surface. Use of Shield n Peel products on these types of surfaces are done so with a clear understanding that the buyer assumes all risks and liabilities for the results of such use. Store for up to 12 months in a clean dry area above 10°C. Keep the lid sealed in and airtight when not in use. DO NOT allow product to freeze.

Warranty: Guru Corporation PTY LTD makes no warranties, expressed or implied including but not limited to, the implied warranties of merchantability and fitness for a particular purpose. Suggestions and recommendations are made without warranty or guarantee of any kind. The buyer assumes all risk and liability for the results of such use. Guru Corporation PTY LTD, ABN: 83 096 593 092. Unit 2 / 872 Pacific Highway, LISAROW NSW 2250, AUSTRALIA. Made in AUSTRALIA.

SHIELD n PEEL®

SHIELD IT TO PROTECT IT

PEELSTRIP



SHIELD n PEEL PEELSTRIP

is a water-based, viscous clear gel product specially developed for the removal of temporary protective coatings (TPC).

The thixotropic nature of the product provides excellent clinging on vertical surfaces to provide sufficient contact time for temporary protective coating removal.



GOOD FOR REMOVING

SHIELD n PEEL for WINDOWS
SHIELD n PEEL for BATH & SPA ACRYLIC
SHIELD n PEEL for FLOORS
SHIELD n PEEL PAINTSHIELD
SHIELD n PEEL for METAL BATH

SHIELD n PEEL PEELSTRIP is specially formulated to assist in breaking down hard to remove or baked on temporary surface protection products. Apply a thick coating over the stubborn area and allow time for SHIELD n PEEL PEELSTRIP to react. WE recommend a minimum of 30 minutes to several hours depending on thickness of surface protection. SHIELD n PEEL PEELSTRIP will turn the surface to a semi liquid state making it possible to remove any unwanted or incorrectly applied product.

For "How to Apply" videos & more info on all our products: www.shieldnpeel.com.au



www.gurucorp.com.au
Unit 2 / 872 Pacific Highway
TUGGERAH NSW 2250
Ph 1300 852 646

SHIELD n PEEL®
SHIELD IT TO PROTECT IT

GHS Precautionary Statements

- P210: Keep away from heat/sparks/open flames/hot surfaces – No smoking
- P233: Keep container tightly closed
- P243: Take precautionary measures against static discharge
- P261: Avoid breathing dust/fume/gas/mist/vapours/spray
- P262: Do not get in eyes, on skin, or on clothing
- P280: Wear protective gloves/protective clothing/eye protection/face protection
- P303+361+353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
- P371+380+375: In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion
- P501: Dispose of contents/container in accordance with local/regional/national regulations

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

List

| Chemical Name(s) | CAS Number | % Weight |
|------------------|------------|----------|
| ETHYL LACTATE | 687-47-8 | 40-60 |
| WATER | 7732-18-5 | 50-60 |
| ADDITIVES | PROPRIETOR | 1-10 |

SECTION 4 - FIRST AID MEASURES

General Advice If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.

Eye Contact: Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eyes wide open while rinsing. Call a physician immediately.

Skin Contact: Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

Inhalation: Move to fresh air in case of accidental inhalation of vapors. If symptoms persist, call a physician.

Ingestion: Clean mouth with water and afterwards drink plenty of water. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Consult a physician.

Notes to Physician Treat symptomatically.

Protection of First-aiders Use personal protective equipment. Avoid contact with skin, eyes and clothing.

SECTION 5 - FIREFIGHTING MEASURES

Flammable Properties: Flammable. Vapors may form explosive mixtures with air.

Suitable Extinguishing Media Foam. Alcohol-resistant foam. Dry chemical. Dry powder. Carbon dioxide (CO₂). Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Cool closed containers exposed to fire with water spray.

Unsuitable Extinguishing Media: Do not use a solid water stream as it may scatter and spread fire.

Hazardous Combustion Products: Burning produces irritant fumes, Carbon monoxide (CO), Carbon dioxide (CO₂).

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions: Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges. Use personal protective equipment.

Environmental Precautions: Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

Methods for Clean-up Dam up: Soak up with inert absorbent material. Pick up and transfer to properly labelled containers. After cleaning, flush away traces with water

SECTION 7 - HANDLING AND STORAGE

Handling: Use only in area provided with appropriate exhaust ventilation. Wear personal protective equipment. Do not breathe vapors or spray mist. Use product only in closed system.

Storage: Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat. Protect from light. Keep in properly labelled containers.

SECTION 8 - EXPOSURE CONTROL/PERSONAL PROTECTION

Exposure Limits

This product is not known to contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies.

Engineering Measures: Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal Protective Equipment

Eye/face Protection: Tightly fitting safety goggles.

Skin and Body Protection: Long sleeved clothing, Boots, Apron, Impervious butyl rubber gloves, Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used.

Respiratory Protection: In case of mist, spray or aerosol exposure wear suitable personal respiratory protection.

General Hygiene Considerations When using, do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing

You should call the Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

| | | | |
|---|------------------|------------------------------|---------------------|
| Reactivity In Water - Analytical Voc (Epa Method 24) | None | Ph | Approx 4 |
| Appearance Water | Not Available | Melting Point | Not Available |
| Specific Gravity (H2O=1) | White Liquid Gel | Freezing Point | Same As Water |
| % Volatile By Volume | 1.01-1.03 | Boiling Point | Not Available |
| % Solid By Weight | 50 | Flash Point | Not Available |
| Theoretical Voc | Not Available | Flammability (Liquid) | Flammable On Drying |
| Colour | Not Available | Evap. Rate | Not Available |
| Odor | Colourless | Water Solubility | 100% |
| Odor Threshold | Mild Sweet Odor | Viscosity | Gel viscous |
| | Nonw | | |

SECTION 10 - STABILITY AND REACTIVITY

Chemical Stability: Stable under normal conditions.

Conditions to Avoid: Heat, flames and sparks.

Incompatible Materials: Strong oxidizing agents. Strong acids. Strong bases. Hazardous Decomposition: Products None known.

Possibility of Hazardous Reactions: Hazardous polymerization does not occur

SECTION 11 - TOXICOLOGICAL INFORMATION

Toxicological Information (product): no information available

SECTION 12 - ECOLOGICAL INFORMATION

Chemical 1 Persistence and Degradability Readily biodegradable

Chemical 1 Bioaccumulation Potential No information available

Chemical 1 Mobility Information Miscibility with water

SECTION 13 - DISPOSAL CONSIDERATIONS

Product Disposal Considerations:

Dispose of in compliance with the laws and regulations pertaining to this product in your jurisdiction.

Miscellaneous Advice:

Empty containers should be taken for local recycling, recovery or waste disposal

SECTION 14 - TRANSPORTATION INFORMATION

DOT Domestic Ground: Non-Bulk Non regulated

SECTION 15 - REGULATORY INFORMATION

TSCA: Not reported

SARA TITLE III (313):

This product is not known to contain any chemicals which are subject to the reporting requirements of the Act or regulations contained in 40 CFR 372.

SARA 311/312:

Acute Health Hazard- Yes , Chronic Health Hazard- No, Fire Hazard- Yes, Sudden Release of Pressure Hazard- No, Reactive Hazard- No

HMIS-Health: 2

HMIS-Fire: 1

HMIS-Reactivity: 0


SECTION 15 - REGULATORY INFORMATION

HMS-PPE: As required
NFPA-Health: 2
NFPA-Flammability: 1
NFPA-Reactivity: 0

SECTION 16 - OTHER INFORMATION

SDS Revision: None
Date: 2/1/2017
SDS Author: General Chemical Corp

| | |
|-------------------|--------------------|
| HEALTH | 2 |
| FIRE | 1 |
| REACTIVITY | 0 |
| PPE | As required |



Please read all labels carefully before using product.

SHIELD N PEEL PEELSTRIP is a water-based, viscous clear gel product specially developed for the removal of temporary protective coatings (TPC). The thixotropic nature of the product provides excellent clinging on vertical surfaces to provide sufficient contact time for temporary protective coating removal. SHIELD N PEEL PEELSTRIP is specially formulated to assist in breaking down hard to remove or baked on temporary surface protection products. SHIELD N PEEL PEELSTRIP will turn the surface to a semi liquid state making it possible to remove any unwanted or incorrectly applied product.

GOOD FOR REMOVING

SHIELD n PEEL for WINDOWS

SHIELD n PEEL for BATH & SPA ACRYLIC

SHIELD n PEEL for FLOORS

SHIELD n PEEL PAINTSHIELD

SHIELD n PEEL for METAL BATH

'Saves you time and money by eliminating costly replacement'

- * Water-based
- * Non-flammable
- * Non-hazardous
- * Biodegradable
- * Easy to apply & remove

TEST AREA

Always test a small inconspicuous area first. Because of various substance characteristics and conditions like porosity, deterioration, embattlement, adverse wear area, type of ink, paint and or other coating applied, abrasion of panted surfaces, and the like, it is difficult to predetermine specific effects from this product.

PREPARATION

- Application Surface **must** be clean & dry
- Use drop sheets and tape to protect nearby surfaces
- **Tools needed:**
Roller with a 20mm polyester NAP or brush or cloth.

APPLICATION

- Easy to apply by roller or brush. Apply 10 MILS thick wet coating on the temporary protective coating to be removed.
- Ensure adequate ventilation when applying product

REMOVAL

- Rinse with a room temperature or warm water using a hose or pressurised water spray.
- SHIELD N PEEL PEELSTRIP is specially formulated to assist in breaking down hard to remove or baked on temporary surface protection products. SHIELD N PEEL PEELSTRIP will turn the surface to a semi liquid state making it possible to remove any unwanted or incorrectly applied product.

PRECAUTION

- Avoid skin and eye contact.
- Chemical goggles and impervious gloves should be worn when handling this product.
- Avoid breathing vapors that occur during application. A painters mask or other suitable respiratory device should be work when applying this product
- DO NOT ALLOW PRODUCT TO FREEZE

CLEAN UP / WASTE

- Wash up in water
- DO NOT pour contents or washings down drains or sinks. Dispose of as per your local council regulations.

COLOUR

SHIELD N PEEL PEELSTRIP is a viscous clear gel

SHELF LIFE / STORAGE

- Will keep up to 12 months if stored in a clean dry area above 10°C.
- Keep the lid sealed airtight when not in use.

DATASHEET

MARCH 2022

PEELSTRIP

SDS

DATASHEET

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

SHIELD N PEEL PEELSTRIP

PRODUCT USE

Paint Remover.

SUPPLIER

Company:
Guru Corporation Pty Ltd
ABN: 83 096 593 092
Address: Unit 2 / 872 Pacific Highway, LISAROW NSW 2250, AUSTRALIA
Telephone: +61 2 4353 9660
Fax: +61 2 4353 9466

HAZARDOUS MATERIALS DESCRIPTION, PROPER SHIPPING NAME, HAZARD CLASS, HAZARD ID NO.

Non-hazardous

ADDITIONAL HAZARD CLASSES

Not regulated

CHEMICAL FAMILY

Coating Remover

SECTION 2 - HAZARD IDENTIFICATION

GHS Hazard Categories

Serious eye damage/eye irritation Cat 1
Specific target organ tox, single exp. Cat 3 (resp irrit)

SECTION 2.2 - GHS LABEL ELEMENTS

GHS Signal Word Warning



GHS Hazard Statements

- H318: Causes serious eye damage
- H319: Causes serious eye irritation
- H335: May cause respiratory irritation